





Installation: Drop-in cannot be under mounted

GENERAL SPECIFICATIONS:

Material Acrylic Plumbed Weight : 145lbs / 66 kg Soaker Weight : 115 lbs / 52 kg Average Fill: 65 gal to above jet level

ELECTRICAL SPECIFICATIONS:

Required Electrical	Service 110 Volt
Air Bath or Whirlpool	1-15 amp GFCI
Whirlpool with Inline Heater	1-20 amp GFCI
Dual Bath	1-20 amp GFCI
Soaker	-

PACKAGES AND OPTIONS		
Hydrotherapy Package	Package Contents	Part #
Soaker	soaking bath - no jets, textured bottom	4272WS
Whirlpool	8point-massage jets, 1-hp pump, textured bottom	4272WH
Air Bath	12 air jets, air blower, textured bottom	4272WA
Dual Bath	8 point-massage jets, 1-hp pump, 12 air jets, air blower, textured bottom	4272WD

OPTIONS Colors Available - White Biscuit Quick Ship - reduces lead time - call for availability Inline Heater with Pump - Whirlpool or Dual Bath Lift & Turn Drain Kit -Chrome,Brushed Nickel, White

IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Add bedding compound to fully level and support bottom of tub.
- Tubs equipped with an air bath or a pre-leveled foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Please measure tub on-site before building tub decking.
- Jet, pump & blower locations are predetermined and cannot be changed.
- Suction and control locations may vary.
- Specifications and configurations are subject to change without notice.
- Measurements are +1/2" and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.

©2013 by SPA WORLD CORP Modification Rights Reserved.