

6060C

 $59\frac{1}{4}$ " x $59\frac{1}{4}$ " x 23"

Installation: Drop-in cannot be under mounted

GENERAL SPECIFICATIONS:

Material Acrylic

Plumbed Weight: 150 lbs /68 kg Soaker Weight: 120lbs / 54kg Average Fill: 75 gal to above jet level

ELECTRICAL SPECIFICATIONS:

Required Electrical Air Bath or Whirlpool Whirlpool with Inline Heater Whirlpool and Air Service 110 Volt 1-15 amp GFCI 1-20 amp GFCI 1-20 amp GFCI

Soaker

PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
Soaker	Soaking bath - no jets, textured bottom	6060CS
Whirlpool	Adjustable pointed-massage jets, 1-hp pump, textured bottom	6060CH
Air Bath	Air jets, Air blower, Textured bottom	6060CA
Whirlpool and Air	Adjustable pointed-massage jets, 1-hp pump, Air jets, Air blower, textured bottom	6060CD

- OPTIONS
- Colors Available White Biscuit
- Quick Ship reduces lead time call for availability
- Inline Heater with Pump Whirlpool or Whirlpool and Air
- Lift & Turn Drain Kit -Chrome, Brushed Nickel, White
- Color Match Jets.

IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Add bedding compound to fully level and support bottom of tub.
- Tubs equipped with an air bath or a pre-leveled foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Please measure tub on-site before building tub decking.
- Jet, pump & blower locations are predetermined and cannot be changed.
- · Suction and control locations may vary.
- Specifications and configurations are subject to change without notice.
- Measurements are +1/2" and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.